## **Technical Data Sheet**

## ChangFu® VBN32



N-[2-(N-Vinylbenzylamino)ethyl]-3-aminopropyltrimethoxysilane Hydrochloride

**Description** ChangFu® VBN32 is a high-purity styrene amino silane that is primarily used for fiberglass

infiltration and surface treatment. It enhances and improves the adherence of fiberglass to various polymers such as epoxy and phenolic resin. It has been widely employed in the

manufacture of surface treatment agents for electronic glass cloth laminate sheets.

Features & Benefits Quaternary ammonium functionalized trialkoxysilane.

Improve and increase the adherence of glass fiber to epoxy resin.

Reduce plate explosions and flaws during the high-temperature reflow soldering of high-

temperature printed circuit boards.

Applications Used as an essential additive for glass fiber impregnation. It primarily acts as a coupling

agent and adhesion promoter, promoting the adhesion between glass fibers and polymers.

Used as a silane coupling agent for unsaturated polyesters.

Used as a polymerization comonomer.

**Typical Properties** 

| Description | N-[2-(N-Vinylbenzylamino)ethyl]-3-aminopropyltrimethoxysilane Hydrochloride |
|-------------|---|
| Product No. | ChangFu® VBN32  |
| CAS No.     | 34937-00-3  |
| Formula     | C17H31CIN2O3Si  |
| Sales Spec  | 40% in Methanol   |
| Color       | Colorless or light yellow   |
| Appearance  | Clear liquid  |

Package Offered in 25L pails and 200L drums.

Custom packaging is available.

**Storage** Stored in a cool, well-ventilated place.

Keep container tightly closed.

**Transportation** See the corresponding Safety Data Sheet.